

Investigations into Surface Treatment Methods for Reduction of Recontamination of BWR Reactor Systems

Bernhard Stellwag ¹⁾, **Juan de Dios Sanchez Zapata** ²⁾, Ashim Basu¹⁾, Stephan Hoffmann-Wankerl ¹⁾, Luis Sempere Belda ¹⁾, Tomas Berasaluce ²⁾

¹⁾ AREVA GmbH, Erlangen, Germany

²⁾ Iberdrola Generation Nuclear S.A.U., C.N. Cofrentes, Cofrentes (Valencia), Spain

Background (1/2)

- The NPP Cofrentes is a 1100 MW_e-class GE BWR 6, located in Valencia province, East of Spain.
- The plant went commercial in March 1985
- The primary system has two external recirculation loops with Jet Pumps internals to the Reactor Vessel. The system is made of Stainless Steel (SS)
- The Reactor Water Clean Up (RWCU) piping is made of Carbon Steel
- Water chemistry operation history:
 - Zinc injection since June 1996
 - Normal Water Chemistry operation (NWC) until March 1997, Moderate Hydrogen Water Chemistry operation (HWC-M) until April 2010
 - HWC/OLNC/Zn chemistry until today (OLNC™; the process is patented by General Electric).
- The usual cycle length of the plant is 24 months since mid 2000's


Central Nuclear de Cofrentes



Background (2/2)

- The RWCU piping sections upstream the heat exchangers in the NPP Cofrentes were decontaminated with the AREVA CORD® CS process in 2002 (RFO 13), 2005 (RFO 15) and in 2009 (RFO 17).
- A fast and climbing recontamination of the piping sections was observed after each decontamination treatment.
- Transitioning of the plant to HWC/OLNC/Zn operation in 2010 did not result in the expected decrease in dose rates in RFO 18 in 2011.
- The NPP Cofrentes therefore considers another decontamination of the RWCU system in 2015 (RFO 20).

SOURCE TERM EVOLUTION AT RECIRC. LOOPS (B33) & RWCU (G33)



Objective of the reported work

- Elaborate surface treatment methods for prevention of quick recontamination of BWR reactor coolant systems after decontamination treatments
 - Test the mitigation effectiveness of the selected methods by an in-plant exposure program
 - Apply the most effective method after the next decontamination treatment at the plant
-
- The work is performed in a joint R&D program of IBERDROLA, the operator of NPP Cofrentes, and AREVA
 - The work was started in 2013
 - Results after three months exposure of test tubes in the reactor system of NPP Cofrentes are reported in the following slides


Selected surface treatments

- (1) Reference condition for these surface treatments and the in-plant exposure tests ¹⁾:
Carbon steel surfaces representative for decontaminations with the AREVA process CORD[®] CS
- (2) Platinum deposition (so-called Low Temperature NobleChem process LTNC[™], the process is patented by General Electric)
- (3) Application of a Self-Assembling Monolayer SAM (patent application of AREVA GmbH pending)
- (4) Platinum deposition followed by the application of a SAM

¹⁾ The surface treatments were elaborated and applied in a decontamination test facility of AREVA after a previous decontamination treatment

Visual appearance of the samples before in-plant exposure; Mitigation Principles

Post CORD CS treatment Mitigation Principles



- Fe oxide film post decon (i.e. after the Fe oxalate destruction step and system rinse) is desirable for corrosion protection of the carbon steel surfaces until plant start-up after the outage
- Film properties not optimized yet for prevention of activity pick-up (this work)



Visual appearance of the samples before in-plant exposure; Mitigation Principles

Post decon plus Pt



Mitigation Principles

- Positive influence of Pt doping on stainless steel pipe dose rates proven by lab tests and plant operation experience
- Same effect is expected for carbon steel pipe work
- Provide Pt doped surfaces from start of the subsequent fuel cycle (LTNC™ process patented by General Electric)

⇒ Adjustment of Pt treatment parameters to carbon steel required:
Pt content 1 - 2 % by weight
determined by SEM EDX

Visual appearance of the samples before in-plant exposure; Mitigation Principles

Post decon plus SAM



Mitigation principles

- Produce a more compact oxide film: SAM treatment removes loosely adherent oxide particles
- Prevent penetration of oxidants (i.e. O_2 , H_2O_2) and nuclides into the oxide film: SAM treatment produces a water-repellent film on the carbon steel surfaces
- High film durability in water and steam proven by plant operation experience post SAM applications
- High radiation resistance of the films in reactor systems expected

SAM coats Properties and Application



Plant components after SAM treatment

- The coats consist of a water repellent film
- Application possible with decon equipment

Visual appearance of the samples before in-plant exposure; Mitigation principles

Post decon plus Pt & SAM




Mitigation principles

- Same as for Pt and SAM
- ⇒ Is further reduction of recontamination by a combination of the positive effects of Pt and SAM possible?
- Pt loading of the sample:
Platinum content 0.6 – 1.1 % by weight determined by SEM EDX

In-plant exposure tests: Approach

- Use the mitigation monitoring system at NPP Cofrentes for the in-plant exposure tests (MMS panel)
- Installed several sets of test samples during the 19th refueling outage of the plant in Oct. 2013
- Remove and replace the first set before OLNC treatment of the reactor coolant system, three months after start of the 20th fuel cycle
- Remove and replace additional sample sets later in the cycle
- Measure contact dose rates and nuclide-specific activities as a function of the surface treatment methods
- Determine also other properties of the oxide layers before and after in-plant exposure (e.g. Pt loading)
- The test samples were machined from $\frac{3}{4}$ " carbon steel tubes
- The selected carbon steel grade ASME SA179 is representative of the steel grade used at NPP Cofrentes

Location of MMS panel at Cofrentes NPP



MMS Panel (Mitigation Monitoring System)

- Supplied by GE for the OLNC project
- Continuous flow of RWCU pump water
- Works at Reactor Temp. And Pressure
- Provided with a set of Pt Deposition Coupons
- ECP, Temp. and Flow rate Instrumentation

In-plant exposure tests: First Results

Contact dose rates measured three months after BOC

Surface treatment condition	Contact Dose Rate (uSv/h)
Coupon 1-Decon Step	4300
Coupon 2-Pt Treatment	1280
Coupon 3-Pt+SAM Treatm	1490
Coupon 4-SAM	580

- 1st set of coupons removed from MMS panel on Jan 31, 2014
- Dose rates are dominated by Co-60
- Extremely high effectiveness for recontamination reduction confirmed for
 - Pt treatment
 - SAM treatment.
- As of today, both treatment methods are promising options for an application after the next system decontamination at NPP Cofrentes
- Combination of the two methods did not result in a further decrease in contact dose rates as compared to Pt alone

Data provides an excellent basis for further investigations and continuation of the joint R&D program.

Summary and Conclusions

- Pt and SAM treatment methods have been proven very effective for reduction of recontamination of carbon steel
- The effectiveness of the two methods will be confirmed for longer in-plant exposure times
- It is expected that both processes can be applied without difficulties at NPP Cofrentes after a decontamination treatment
- Adaption of the two processes to Cofrentes-specific conditions has to be examined with regard to
 - Time needed for their application
 - Dosing equipment and parameters
 - Process monitoring and control program
 - General robustness of the two processes.

THANK YOU !