

Radiation Protection in the design of the Flamanville 3 EPR

Noëlle EGLIZAUD – Stéphane MOREAU – Yannick BENETEAU

EDF / CNEN



Contents

1. Introduction

2. General layout requirements

1. Radiation protection zoning
2. Specific requirements

3. ALARA at the design stage

1. Approach and methodology
2. Reference dose
3. Initial dose
4. Optimised dose

4. Cleanliness/waste consideration

1. Introduction

The designers:


- **consider the radiation protection at the Safety level,**
- **place the EPR plant in a step of progress compared to the best French nuclear plants**
 - Layout and civil work requirements regarding Radiation Protection
 - Use of the good performances of existing plants and of operational feedback
 - Dose optimisation for the most exposed activities and workers
- **allow the operator to work in the Reactor Building during power operation**
 - In order to improve the plant availability while complying scrupulously with the radiation protection rules

2. General layout requirements: zoning

French Regulatory exposure limits:


- 20 mSv over 12 consecutive months for A classified workers,
- 6 mSv over 12 consecutive months for B classified workers

French Regulatory radiation protection zoning



2. General layout requirements

- ◆ Encasement of active equipment,
- ◆ Good accessibility to equipment requiring regular maintenance,
- ◆ Shielding mazes or shielding doors shall be foreseen to access to active equipment, the corresponding valves are located near the room entrance



- ◆ Sufficient space is foreseen for:
 - A low dose area to prepare and monitor the activities,
 - Maintenance of the equipment in the buildings,

2. General layout requirements: dose limits

- ▶ Hot lab in Operation Building: 7.5 $\mu\text{Sv/hr}$

- ▶ Sampling laboratories in Nuclear Auxiliary Building and frequent passageways (corridors, staircases): 10 $\mu\text{Sv/hr}$

- ▶ 25 $\mu\text{Sv/hr}$ limit for:
 - Access to working areas, safety exits, control valves rooms
 - Edge of the spent fuel pit in the Fuel Building
 - Reactor building at shutdown: edge of the refuelling cavity

- ▶ Reactor building at power, accessible area
 - Neutron dose rate: 2.5 $\mu\text{Sv/hr}$,
 - Effective dose rate: 25 $\mu\text{Sv/hr}$

3. ALARA at the design stage (1/6): approach

O
P
T
I
M
I
S
A
T
I
O
N

Reference collective dose



Design evolutions of the EPR concerning Radiation Protection

- Source Term
- Dose rates
- Exposed time

EPR Initial Dose Assessment



Priority to activities with high dose level (contributing to more than 50 % of collective dose) :

- Thermal insulation
- Opening and closing reactor vessel
- Steam generator controls
- Logistics
- Primary Valves
- Spent fuel Evacuation
- Waste Conditioning



EPR optimised collective dose

3. ALARA at the design stage (2/6): approach

High-dose activities selection:

- Thermal insulation removal and reinstallation
- Site logistics
- RCP, RCV, RIS/RRA [RCS, CVCS, SIS/RHRS] valves

} **High exposed workers**

- Reactor pressure vessel opening/closing
- Fuel evacuation

} **High collective dosimetry**

- SG preparation and tests

} **High dose rate activity**

- Waste conditioning

} **Radiological cleanliness**

50 % of the collective dose

3. ALARA at the design stage (3/6): reference dose

- ◆ The reference dose is based on:
 - The operational feedback,
 - Dose statistics of the best French nuclear plants in operation

- ◆ Recent plants: P'4 (newest 1300 MWe) and N4 (1450 MWe)
 - 18-month cycle
 - Averaged over 10 years
 - Outages cycle:
 - 3 Normal Refuelling Outages (NRO)
 - 2 Refuelling Only Outages (ROO)
 - 1 10-year outage

→ 0.44 Man.mSv/year/unit

3. ALARA at the design stage (4/6): initial dose

▶ Source term

- Significant reduction of stellites™ amount in valves and RPV internals
- Optimisation of the main primary chemistry
 - global profit of 15% in the dose rate

▶ Dose rates reduction

- Pressurizer spray lines separated from pressure relief valves by a concrete shielding
- Reduction of «hot point traps»

▶ Exposed time limitation

- Fast mounting thermal insulation
- Optimisation of steam generator channel head
- Use of valves with modular maintenance

→ **0.36 Man.mSv/year/unit**

3. ALARA at the design stage (5/6): optimised dose

◆ Thermal insulation removal and reinstallation

- Thermal insulation and pipe identification
- Operation with water in the pipes

◆ Site Logistics

- Fast mounting/dismounting scaffolding
- Fix platform around SG manhole, handhole and eyehole

◆ RCP, RCV, RIS/RRA Valves

- Limitation of Stellite™ amount
- Improvement of valves tightness: double leak tightness barrier

◆ Reactor pressure vessel opening/closing

- Core internals handling under water
- Dedicated zone for the vessel header storage

3. ALARA at the design stage (6/6): optimised dose

▶ SG preparation and tests

- Fast mounting nozzle dams
- Increase of the primary/secondary manholes diameters

▶ Waste conditioning

- Waste selection near their production location
- Possibility to check the waste conformity in the NAB

▶ Fuel evacuation

- Help for the fuel trolley positioning

+ Access in the Reactor Building during power operation

Reference collective dose

0.44 Man.Sv/yr/unit



Design evolutions of the EPR concerning Radiation Protection

- Source Term
- Dose rates
- Exposed time

EPR Initial Dose Assessment

0.36 Man.Sv/yr/unit



Priority to activities with high dose level (contributing to more than 50 % of collective dose) :

- Thermal insulation
- Opening and closing reactor vessel
- Steam generator controls
- Logistics
- Primary Valves
- Spent fuel Evacuation
- Waste Conditioning



EPR collective dose = 0.35 Man.Sv/yr/unit

4. Cleanliness/waste consideration

► Basis concept: controlled zone \neq contaminated zone

► Goals

- To get a radiological cleanliness at the best international operators level
- To adapt the protection to the contamination risk identified where the action takes place and limit the contamination at its source
- To facilitate the access and working conditions in the controlled zone
- Be a mean of progress in the plant cleanliness: the zoning has to be maintained

► At the design stage,

■ It required a general contamination view:

- Identification of the nuclear / conventional areas (N vs K) → Regulatory
- Evaluation of the contamination level in the nuclear areas (Np, N1, N2)

} Cleanliness/waste zoning

■ It led to requirements regarding:

- Ventilation routing
- Contamination containment
- Operators access



The Cleanliness/waste zoning is a tool for the plant design. The operator can apply it or not.

Methodology:

1. Classification of each room based on: the systems installed, the actions to be performed, the waste produced...
2. Evaluation of the overall building level to have a consistent zoning with the operation: routing from the less contaminated to the most
3. Implementation of contamination barriers

Zone	Conventional waste zone	Nuclear waste zone		
Waste zoning	Conventional: K	Nuclear: N		
Cleanliness zoning	K Conventional	Np Nuclear clean	N1 Nuclear slightly contaminated	N2 nuclear contaminated
Room surface contamination (Bq/cm ²)	< 0.4 No neutron flux	< 0.4	0.4 < conta. < 4	> 4
Cleaning and control	Cleaning program Cleanliness periodic tests program			No cleaning and test program

Clean (green arrow pointing to the K zone)

Contamination barrier (red arrow pointing to the barrier between Np and N1)

No-clean (red arrow pointing to the N2 zone)

4. Cleanliness/waste consideration

◆ Reactor in operation

- « in blue » access to K and Np zones, including the RB accessible area
- Over clothes put at the N1 and N2 contamination barriers

◆ Reactor at shutdown

- The reactor building is N1 or N2
- The over clothes for activities in the RB are taken in the Access tower and completed at the RB entrance
- The over clothes are left at the RB exit

◆ The « in-blue » access is reversible:

- « cold » changing rooms kept in the Operation Building
- « hot » changing rooms operate (level -2)
- all the devices and systems are foreseen, the ventilation is designed as for « in-white » access, decontamination showers are implemented

5. Conclusion

The Flamanville 3 EPR designers considered:

- the radiation protection Regulatory requirements
- specific radiation protection requirements
- the ALARA approach
- the contamination containment and limitation

to place the EPR into an evolutionary approach

FA3, general view



FA3: Reactor Building



FA3: pumping station



Radiation Protection in the design of the Flamanville 3 EPR

Thanks for your attention



CHANGER L'ÉNERGIE ENSEMBLE