



KINECTRICS



Characterization of Radiation Fields for Dose Reduction During Outages at Darlington Nuclear Station

Yury Verzilov and Aamir Husain

Kinectrics Inc.

Tom Wong

Ontario Power Generation, Darlington Nuclear

*2009 ISOE International ALARA Symposium
IAEA HQ, Vienna, Austria • 13 – 15 October, 2009*

Presentation Flow



- I Introduction**
- II Methodology for Outage Activity Transport Monitoring (OATM) surveys**
- III Selected results from OATM surveys**
- IV Application of results for dose reduction during outages**
- V Conclusion**



KINECTRICS

Ideas Into Energy®



Toronto, Canada
www.kinectrics.com

OATM Surveys for All
CANDU Stations in Ontario

Deposition of radionuclides on out-of-core surfaces leads to:

- a) growth of station gamma fields, and
- b) effect on worker dose




Major contributors to external radiation fields around station components:

- Activated transition metals: ^{60}Co , ^{58}Co , ^{51}Cr , ^{54}Mn , ^{59}Fe
- Radioantimony group: ^{122}Sb , ^{124}Sb , ^{125}Sb
- Nb/Zr group: ^{94}Nb , ^{95}Nb , ^{95}Zr
- Fission product group: ^{137}Cs , $^{140}\text{Ba}/^{140}\text{La}$, ^{103}Ru , ^{106}Rh


CANDU Station



Primary Heat Transport System



Moderator System



Outage Activity Transport Monitoring



Objective

Identification of radionuclides responsible for observed radiation field *and their specific activities*

Approach

In-situ gamma spectroscopy and dose rate measurements coupled with interpretation method

Approximations

- Radionuclide identification based on photopeak in measured gamma spectrum
- Interpretation method based on radiation field model of reactor component
- Radiation field simulated by MICROSHIED (single-source scene) / MERCURAD (multi-source scene)

Why OATM Surveys are Required




Effective way to meet the ALARA principle:

- Short-term strategy – Minimize worker dose from existing radiation sources;
- Long-term Strategy – Develop and put in place radiation source term reduction technologies

OATM Surveys can Provide:

- Radiation job optimization with regard to radioprotections and cost;
- Evaluation of effectiveness of the radiation source term reduction technologies

Example for a Steam Generator – Darlington NGS



Modeling

- ✓ Representative structure
- ✓ Sensitivity analysis
- ✓ Measurement conditions


Measurements

- ✓ Dose rate distribution
- ✓ Spectroscopy data

Analysis


- ✓ Specific activities
- ✓ Dose rate
- ✓ Measured/Calculated

Steam Generator – Dose Rate Distributions




Levels above the T/S

- 1.1 m
- 4.5 m
- 6.5 m



Cold Leg Hot Leg

All contact readings in mrem/h



Divider Plate

SG State

- Empty
- Full


Steam Generator – Radionuclides



Darlington / Unit 1

SG # 4

SG state – Full



Elev.	Cold Leg	Hot Leg
117		
122		


Steam Generator – Dose Contributors



Darlington / Unit 1

SG # 4



SG state – Full




Elev.	Cold Leg	Hot Leg
117		
122		

Bleed Cooler Radiation Field

Darlington NGS Unit 1




Surveys in the Reactor Vault



VFC – Vertical Feeder Cabinet;

RF – Reactor Face

Reactor Vault – Dose Rate Distributions




D811 Outage

Row / Elevation

A / 107.5

M / 104.2

Y / 100.9




Radiation Field across the Reactor Face




D811 Outage

East Face —
West Face —

Variation across
Columns
(Left to Right)



Variation across
Rows
(Top to Bottom)



Reactor Vault – Radionuclides




D811 Outage

Reactor Face

East

West




Reactor Vault – Dose Contributors




D811 Outage


Reactor Face
East West




3-D Model of Reactor Face Top



3-D Model of End Fitting Cell




Cell Surveys and Shielding Blocks



Shielding Block:

30cm x 30cm;
Hole ~ Ø 18cm;
Weight ~ 12kg




Easy Install:


Block ~ 15 sec

Shielding Factor ~ 4

Overhead Shielding on Reactor Face



Prototype Shielding Structure



Overhead Shielding Concept

Conclusions



- ✓ **OATM surveys provide:**
 - **comprehensive interpretation of observed radiation fields;**
 - **data for 3-D radiation field model of the reactor component;**
 - **consistent comparisons between survey data for various components, reactor units & stations;**
 - **radionuclide information to estimate effectiveness of source term reduction technologies.**

Conclusions (cont'd)



- ✓ **3-D Model of reactor face radiation field was developed to optimize the shielding structures**
- ✓ **Shielding structures, EF shield block and cabinet, have been successfully used in recent outages and led to significant dose savings**
- ✓ **Engineering design of large-scale overhead shielding is in progress for future outages.**