



Schweizerische Eidgenossenschaft
Confédération suisse
Confederazione Svizzera
Confederaziun svizra

Swiss Confederation
Swiss Federal Nuclear Safety Inspectorate ENSI



Filtered Containment Venting Systems at Swiss NPPs and KKL in particular

January 15, 2014, Ft. Lauderdale

J. Hammer, ENSI, and A. Ritter, KKL



Agenda



- Swiss Nuclear Power Plants
- Filtered Containment Venting Systems (FCVS)
- Current Venting Systems in Swiss NPPs
KKB, KKG and KKM
- The FCVS at Leibstadt NPP




The four Swiss NPPs





Nuclear Installations in Switzerland

- NPPs
- Research Reactors
- Interim Storage





Mühleberg Nuclear Power Plant (KKM)



Copyright KKM

BWR

Start of commercial operations:
1972

Net electrical output:
355 MW_{el}

End of operations
scheduled for 2019



Gösgen Nuclear Power Plant (KKG)



Copyright KKG

PWR

Start of commercial operations:

1979

Net electrical output:

985 MW_{el}



Beznau Nuclear Power Plant (KKB 1 & 2)



Copyright KKB

PWR

Start of commercial operations:

KKB 1: 1969

KKB 2: 1971

Net electrical output:
380 MW_{el} each



Leibstadt Nuclear Power Plant (KKL)



BWR

Start of commercial
operations:

1984

Net electrical
output:

1220 MW_{el}



May 2011: No nuclear new build!





Filtered Containment Venting





Philosophy of Filtered Containment Venting

- i. Filtered Containment Venting (FCVS) is a measure for beyond design basis accidents.
- ii. The FCVS is in general passive and does not depend on any external input such as actuation, mechanical movement or supply of power.
- iii. The FCVS is important to safety; its malfunction could lead to radiation exposure of members of the public.
- iv. The FCVS serves mitigate the consequences of a severe accident.
- v. IAEA NS-G-1-10, 4.143 says: Where containment venting systems are installed, the discharge should be filtered to control the release of radionuclides to the environment. Typical filter systems include sand, multi-venturi scrubber systems, HEPA or charcoal filters, or a combination of these. HEPA, sand or charcoal filters may not be necessary if the air is scrubbed in a water pool.
- vi. In case of a severe accident we have to deal with wet and hot gas and air mixtures. Therefore, the FCVS must resist temperatures up to 160°C and high vapor concentration.
- vii. The important nuclides are ^{131}I , ^{134}Cs and ^{137}Cs .
- viii. The FCVS should be designed for heat removal of several MW_{th} during 3 to 5 days



New Guidelines for FCVS (ENSI, preliminary)

- The FCVS is a Safety Relevant System
- In addition to the FCVS, ENSI demands a passive ventilation system without operator action
- The FCVS is always ready during power operation
- Remote and Local operation, RP-conditions
- Simple and passive design, no AC power need
- The gas flow has to be adjustable
- Exhaust via stack, two valve closing system
- Exchange of water and chemicals in the filter during operation should be possible



Design Basis for FCVS (ENSI, preliminary)

- Retention factor >1000 for aerosols
 >100 for elementary Iodine
to be proven by experiments in the range of 30 to 100% of nominal flow
- Filter loading up to 150 kg aerosols
- Probability for containment rupture $< 0.1\%$
- Operating time >100 hours, self-sufficient
- Earthquake resistant as the containment building
- Resistant to pressure peaks
as in case of hydrogen deflagration



Venting Systems at Swiss NPPs





SIDRENT

the FCVS of KKB 1 & 2

Technical Data

max. containment pressure: 3.1 bar nominal,
6.2 bar break down

Rupture Disk nominal pressure: 4.2 bar

Nominal flow rate: 4.5 kg/s

Filter: Air-Lift-Effect

Diameter: 3.5 m

Height: 7 m

water capacity: 30m³

max. Filter loading: 150 kg

max. Temperature: 166°C


Retention factor: >1000 for aerosols
>100 for Iodine (elementary)

Self-sufficient operating time: 24 h



SIDRENT

the FCVS of KKB 1 & 2





KKG Filtered Containment Venting

Technical Data

max. containment pressure: 5.89 bar abs. nominal,

Rupture Disk nominal pressure: 6.5 bar

Nominal flow rate: $\sim 2 \text{ m}^3/\text{s}$

Filter: Venturi Scrubber System

Diameter: 3.0 m

Height: 6.0 m

water capacity: 15 m^3

max. Filter loading: 200 kg

max. Temperature: 160°C


Retention factor: >1000 for aerosols

>100 for Iodine (elementary)

Self-sufficient operating time: 24 h



KKG Filtered Containment Venting Scheme






KKM Filtered Containment Venting CDS

- Technical Data
- max. containment pressure: 9.5 bar
- Rupture Disk nominal pressure: 6.2 bar
- Nominal flow rate: 25 kg/s
- Filter: Multi Venturi Scrubber System
- Outer torus water capacity: 1000m³
- Retention factor: >1000 for aerosols
- >100 for Iodine



KKM - CDS





KKL-FCVS

Actual Filtered Containment Venting System


- Layout
- Efficiency
- Radiological Impact

Planned Improvements

- Hydrogen Problem
- Radiation Monitor
- Filter Long Term Retention



Filtered Containment Venting System Scheme




- Scrubber construction ensures 5 sec residence time allowing for Iodine reaction to complete
- 12 radial branches equipped with nozzles (92 nozzles per filter) expand the gas-steam mixture into aerosol-carrying bubbles



Layout

Clean gas
to stack



Designer: Sulzer / EWI

Rupture Disc Pressure [bara]: 3.1

Operating Pressure [bara]: 2.55

Comissioning: 1993

Max Flow [kg/s]: 20.66


Nominal flow [kg/s]: 13.77




FCVS Efficiency

Activity release (“source term”) after postulated core melt accident

Without Filter (“Fukushima”)



With FCVS Filter (“KKL”)







Simulation: 1 Year Committed Dose


Without Filter (“Fukushima”)

With FCVS Filter (“KKL”)






Radiological Impact of Loaded Filters: Direct radiation very well shielded by





Problems with Existing Configuration: Possible Hydrogen Explosion



- Hazard of Explosion due to Hydrogen Input into Stack
- Calibration of Rad Monitor not easy due to difficult Geometry

Exhaust Line from Filters to Stack



Radiation Monitor



Difficulties with Source Term Estimation

- Sampling not possible, very high Dose Rates of Samples and inside Stack
- Radiation Monitor is measuring Dose Rate [mSv/h], resp. [R/h]
- Conversion Factor Dose Rate to Source Term
 - [mSv/h] → [Bq/h], resp. [R/h] → [Ci/h]
 - Conversion Factor is depending on Energy of Nuclide-Mixture and Stack Ventilation Rate: Depending on Accident Conditions and elapsed Time (rad. Decay).
 - Conversion Factor is averaged for many different Accident Conditions over first 8 hours: $5E11$ (Bq·h/Sv·m³)
 - Stack Flow may be not well defined under Accident Conditions
- Radiation Monitor needs to be relocated

New Pipe Routing outside Stack, new Rad Monitor Location



- No Hydrogen Input into Stack:
No Explosion Hazard
- New Location of Rad Monitor
(inside or outside of Stack Wall)
- Easy Calibration due to well
defined Geometry

Radiation Monitor




Filter Long Term Retention

Activity release (“source term”) after postulated core melt accident

Change in Filter Chemistry under
Consideration:
Long Term Retention of Organic
Iodine (CH_3I) possible

With FCVS Filter (“KKL”)





Conclusions

- Filtered Containment Venting System were implemented 20 years ago in all Swiss NPP
- FCVS turned out to be very helpful in the Post-Fukushima Safety Evaluations
- Improvements concerning Hydrogen, Earthquake Resistance, and Source Term Evaluation under way



for more information please visit:



www.kkl.ch



www.ensi.ch

www.ifsln.ch

A scenic photograph of the Matterhorn mountain peak, partially covered in snow, reflected in a calm lake. The sky is a clear, light blue. The text "Thank you for your attention!" is overlaid in the center of the image.

Thank you for your attention!