

Inside and outside – A review of the RCA boundary

ZF

Dr. Ivo Stalder, RP Department

Andreas Ritter Leibstadt NPP

ZW2

ZL4 ZL3




2012 ISOE European Symposium

Overview

- Initiating events
- Requirements
- Procedure
- Results
- Conclusions




Initial event 1: Hot workshop intake air chiller drain



Initial event 2: Cold condensate storage tank vent

- Cold condensate containing I-131 • after fuel failures
- Changes in water level push lodineair out of tank vents
- Contamination found outside RCA



A review of the RCA boundary ?

- ENSI = Swiss Federal Nuclear Safety Inspectorate
- ENSI-requirement: "A comprehensive review of the entire RCA boundary has to be performed"
- Guideline requirement: "Radioactive effluents may cross the RCA-boundary only on licensed pathways, controlled and compared to release limits"
 - Licensed pathways: Ventilation to stack, Radwaste discharge
 - Controlled: Any instrument reading [cps]
 - ☆ Compared to release limits: qualified sampling and counting reading [Bq]


Agreement with ENSI

- Identified unlicensed pathways with existing release: reportable event
 - Existing release = contaminated pathway
 - Amount of release doesn't matter. Everything above background.
- Identified unlicensed pathways without release
 - Reporting on a monthly basis
 - Not a reportable event
 - Aim: No penalty for serious review

Interfaces between radioactive and non-radioactive systems

- Self-Assessment: "Some interface do not have isolation provisions to prevent contamination of the non-radioactive system"
- What is an "isolation provision" to provide a "safe" interface?
- A safe interface consists of two barriers (two-barrier-concept):
 - A Check-valve
 - ☼ A reliable pressure difference
 - Integrity of component (like a tight heat exchanger tube)
 - Radiation monitor in non-radioactive system (Only under certain circumstances)

Additional tasks:





Review of RCA - Penetrations: Procedure


1. Search and identification of penetrations through RCA - boundary

- 1) Walk Downs in the field
- 2) Discussions with RP/Engineering-staff to gather operational experience
- 2. Verify the the identified penetrations in the as-built documentation
- 3. Assessment of the findings
- 4. Suggest technical solutions to improve unacceptable situations
- 5. Report to Plant Safety Committee and ENSI
- 6. Follow up of plant modifications




Penetrations: Turbine building findings


- A total of 205 penetrations were evaluated
- Rainwater drain lines crossing the RCA







Penetrations: cold condensate storage building



- New roof
- New ventilation
- New coating inside
- 2 million Euros
- New part of the RCA






Penetrations: joint between buildings without seal

Open joint without seal

- Due to the negative pressure inside RCA an inward flow could be demonstrated
- Joints were repaired

Joint with damaged seal

Different types of penetrations



Penetrations: Conclusions

- 1007 penetrations were examined
- 84 penetrations needed corrective action, 52 of them completed




Interfaces: Findings in the turbine building

- Make up water outlets:
 - o Coupling fits to various types of hoses
 - o 1. Barrier = pressure difference
 - o 2. Barrier = non existent



- o Possibility to inject contaminated water into the make up water system
- o Solution: Additional check valve for each outlet



• Underlying problem:

- o Non radioactive systems, whose content is used inside and outside of RCA
- o Examples: fire water, make up water, aux steam, compressed air, service air

Interfaces: Findings in the Radwaste

- Interface between cold condensate (radioactive) and make up water (nonradioactive):
 - o 1. barrier = non existant (similar system pressure)
 - o 2. barrier = non existant
- Valves are not considered to be a barrier, because their position can be "open" or "closed"



Interfaces: Special situations

• Some parts of systems can't be protected with reasonable effort

- Drinking water system inside Hot Lab
- Water supply of Hot Laundry
- Parts of Auxiliary steam system

- Those parts of systems are "sacrificed"
 - Possible contamination is taken into account
 - Documentation for future modifications and decommissioning



The next significant plant modification

- Piping with radioactive content outside RCA
- Flange = Risk for leckage
- Drain to river
- Solution: reroute ventilation and drain discharge towards RCA






Work progress

• Review completed

- o Hot workshop
- o 10 kV-Switchyard
- o Cold condensate storage
- o Turbine building
- o Seismic gap between buildings
- o Steam tunnel
- o Off-gas building
- o Radwaste building
- o Special Emergency Heat Removal building
- o Reactor building
- o Fuel handling building
- o Waste storage building
- Review in progress
 - o Auxiliary building



Conclusions

- Until now a workload of 7 man-years was generated
- Approx. 93 % of the project is completed
- Two dozen of plant modifications has been triggered
- The understanding in plant and systems design has improved among engineers and Radiation Protection
- KKL has become safer with regard to inadvertent release of radioactive material

nkraftwerk Leibstad

• Next time we do it better:

New waste storage building

2012 ISOE European Symposium